

**12 Ton Heat Recovery Outdoor Unit - 460 VAC, 3-Phase, 60Hz  
2X (AOUA72TLCV)**

<b>Job Name</b> _____	<b>Date</b> _____
<b>Location</b> _____	<b>Approval</b> _____
<b>Engineer</b> _____	<b>Construction</b> _____
<b>Submitted To</b> _____	<b>Unit No</b> _____
<b>Submitted By</b> _____	<b>Drawing No</b> _____
<b>Reference</b> _____	

- Inverter driven compressor
- New style high power DC fan motor.
- Blue fin heat-exchanger (Corrosion resistance)
- 10 year Extended Warranty on parts and compressor. See Warranty Statement.
- Optional: Internet, BACnet, LonWorks, or Modbus communication.
- Outdoor separation tube must be ordered separately (UTP-DX567A).



CAPACITY	
Nominal Cooling Capacity - BTU/h [kW]	144,000 [42.2]
Nominal Heating Capacity - BTU/h [kW]	162,000 [47.5]
Nominal Tonnage - Ton(s)	12
Maximum Connectable Indoor Units	22
Connectable Capacity	50% to 150%
Cooling Power Input - kW	11.69
Heating Power Input - kW	12.73
Unit Group	2X (AOUA72TLCV)

OPERATING TEMPERATURES	
Operating Temp. Cooling (DB) - °F [°C]	14 to 115 [-10 to 46]
Operating Temp. Heating (DB) - °F [°C]	-4 to 70 [-20 to 21]
Operating Temp. Cooling/Heating Simultaneous - °F [°C]	14 to 70 [-10 to 21]

ELECTRICAL	
Electrical Power Requirements	460 VAC, 3-Phase, 60Hz
Voltage Range	414 to 506 VAC
Maximum Circuit Breaker - A	2X (25)
Minimum Circuit Ampacity (MCA) - A	2X (21)
Cooling Power Input - kW	11.69
Heating Power Input - kW	12.73
Maximum Starting Current (MSC) - A	2X (16.8)
Compressor - Rated Load Amperage (RLA) - A	2X (8.5)
Fan Motor - Full Load Amperage (FLA) - A	2X (1.5)

EFFICIENCY	
EER Cooling (Ducted/Non Ducted)	11.40 / 11.40
IEER Cooling (Ducted/Non Ducted)	20.4 / 22.2
COP / High Heating 47°F (Ducted/Non Ducted)	3.44 / 3.44
SCHE (Ducted/Non Ducted)	22.2 / 22.2

COMPRESSOR	
Compressor Type	2X Rotary Inverter
Refrigerant Type	R410A
Refrigerant Charge - lbs [kg]	2X (26.01 [11.80])
Compressor Crankcase Heater - W	2X (2X 35)
Refrigerant Oil / Lubricant	POE
Compressor Capacity Control - Steps/Range	951 / 20 - 115 (per unit)

WIRING	
Communication Cable	LonWorks (Fujitsu Pink Cable. See AE Bulletin 009)

FAN	
Fan Type	2X Propeller fan
Fan Airflow Rate - CFM [m3/h]	2X (6,533 [11,100])
Fan Power Output - W	2X (750)
Fan Motor - Full Load Amperage (FLA) - A	2X (1.5)
External Static Pressure (Max) - in.WG [Pa]	0.32 [80]

PIPING	
Max. Total Refrigerant Line Length - ft [m]	3,280 [1,000]
Max Height Diff. (OD & ID) (Upper/Lower) - ft [m]	164/131 [50/40]
Max. Refrig. Line Length 1st Sep. tube & furthest IU - ft [m]	196 [60]
Pipe Connection Method: Liquid/Gas	Brazed
Pipe Connection: Liquid - in [mm]	1/2 [12.70]
Pipe Connection: Discharge Gas - in [mm]	7/8 [22.22]
Pipe Connection: Suction Gas - in [mm]	1-1/8 [28.58]

HEAT EXCHANGER	
H. E. Pipe Type (Material)	Grooved H-pin (Copper)
H. E. Fin Tube (Material)	Corrugate (Aluminum)
H. E. Fin Surface Treatment	Corrosion resistance (Blue fin)
H. E. Fin Pitch - FPI [mm]	18 [1.45]
H. E. Rows x Stages	2X (3 x 60)
H. E. Face Area - Ft² [m²]	2X (23 [2.2])
H. E. Length - in [mm]	2X (69-5/16 [1760])

SOUND	
Sound Pressure Levels (Cooling/Heating) - dB(A)	60 / 61

WEIGHT	
Net Weight - lbs [kg]	2X (609 [276])
Gross Weight - lbs [kg]	2X (653 [296])

DIMENSIONS	
Dim.Net (HxWxD) - in [mm]	2X (66-9/16 x 36-5/8 x 30-1/8 [1690 x 930 x 765])

Dim.Gross (HxWxD) - in [mm]	2X (71-5/16 x 39-7/16 x 33-3/8 [1811 x 1002 x 847])
-----------------------------	---

CODE	
ETL	3170288
AHRI Certified	Standard 1230

Note: Specifications are based on the following conditions:  
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).



Fujitsu General America, Inc.  
 353 Route 46 West  
 Fairfield, NJ 07004  
 Toll Free: (888) 888-3424  
 Fax: (973) 836-0453  
 www.airstagevrf.com

DIMENSIONS

Unit: In. (mm)

